



NOTES:  
 DETAILS ARE NOT TO SCALE  
 Cr<sup>+6</sup> = HEXAVALENT CHROMIUM  
 HDPE = HIGH-DENSITY POLYETHYLENE  
 MG/KG = MILLIGRAMS PER KILOGRAM

**1** 84 FORREST STREET LOADING DOCK  
 FIG. 7-1

- LEGEND**
- APPROXIMATE LOCATION OF CONCRETE CHIP SAMPLES EXCEEDING 20 MG/KG FOR Cr<sup>+6</sup>
  - APPROXIMATE LOCATION OF SOIL SAMPLES EXCEEDING 20 MG/KG FOR Cr<sup>+6</sup> 4' TO 6' BELOW THE CONCRETE SLAB OF THE LOADING DOCK
  - EXTENT OF EPOXY COATING INSTALLATION ON LOADING DOCK HORIZONTAL SURFACE AND STAIRCASE

|   |               |  |
|---|---------------|--|
| PPG<br>FORREST CURRENT-USE REMEDIATION AREAS<br>JERSEY CITY, NEW JERSEY |               | REMEDIAL ACTION WORK PLAN<br>DETAILS: 84 FORREST STREET LOADING DOCK |
| DATE: 03/06/2019  | DRWN: JK, ALC | FIGURE 7-2   |